

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

What is claimed is:

Claims 1-16. Canceled.

17. (New) A method for rendering three-dimensional scenes on a display of a computing device, the method comprising:

rendering the three dimensional scenes, by the computing device, by means of ray-tracing;

establishing, by the computing device, a ray-tracing acceleration structure having a plurality of objects;

traversing, by the computing device, a ray through the acceleration structure until an object of intersection is identified;

storing, by the computing device, the object in a list; and

preventing, by the computing device, the object from being intersected more than once by the ray.

18. (New) The method of claim 17 further comprising:

determining, by the computing device, if an affirmative decision is possible as to whether a triangle within the ray-tracing acceleration structure overlaps a node of the acceleration structure, the decision being based at least in part on comparisons of the vertices of the triangle with the vertices of the node; and

if the affirmative decision is not possible, deciding, by the computing device, by making a conservative decision as to whether the triangle overlaps the node.

19. (New) The method of claim 17 further comprising:

computing, by the computing device, a three dimensional ray space occupied by a ray according to the ray's increasing distance from a virtual source;

traversing, by the computing device, the ray space; and
processing, by the computing device, selected objects identified within the ray space.

20. (New) The method of claim 19, wherein the ray space is a selected one of a cone or a pyramid, and the method further comprises processing, by the computing device, objects within the ray space, and ordering the objects according to the objects' virtual distances from the virtual source of the ray.

21. (New) The method of claim 19, wherein the ray-tracing acceleration structure further comprises at least one acceleration structure node, with each node being associated with a region of node space, and the method further comprises:

storing, by the computing device, simplified geometry data associated with each acceleration structure node; and

computing, by the computing device, a ray-object intersection, using the simplified geometry data to compute the ray-object intersection when the ray space overlaps a majority of the node space.

22. (New) The method of claim 17 further comprising:

subdividing, by the computing device, the plurality of objects into an n-level hierarchy of objects and sub-objects;

classifying, by the computing device, the objects as primitive or non-primitive; and, after traversing a ray through the acceleration structure until an intersected object is identified,

if the identified object is not a primitive object, storing, by the computing device, affine transformation data which transforms the object and ray into a coordinate system locally associated with the identified object, and traversing the local coordinate system and storing affine transformation data, recursively, until the ray intersects with a primitive object; and

if the identified object is a primitive object, storing by the computing device, transformation data which transforms the primitive object and ray into a normalized object space locally associated with the identified object, intersecting the transformed ray with the transformed identified object, and storing, by the computing device, ray-object intersection data.

23. (New) The method of claim 17 further comprising:

subdividing, by the computing device, the plurality of objects into an n-level hierarchy of objects and sub-objects;

recursively instantiating, by the computing device, a plurality of sub-objects, the sub-objects having a similar geometry; and

building, by the computing device, a next level object by, at least in part, using the plurality of instantiated sub-objects with similar geometry.

24. (New) An apparatus for rendering three-dimensional scenes, the apparatus comprising:

a processor;

a tangible computer-accessible storage medium operatively coupled to the processor;

a ray-tracing acceleration structure stored in the storage medium, the acceleration structure having object data for a plurality of objects; and

a ray-casting module operatively configured to traverse rays through the acceleration structure and return ray-object intersection data, the ray-casting module comprising a decision unit operatively configured to prevent objects from being intersected by a ray more than once.

25. (New) The apparatus of claim 24 wherein the ray-casting module further comprises an acceleration structure computation unit operatively configured to:

determine if an affirmative decision is possible as to whether a triangle within the ray-tracing acceleration structure overlaps a node of the acceleration structure, the

decision being based at least in part on comparisons of the vertices of the triangle with the vertices of the node; and

if the affirmative decision is possible, store the affirmative decision as part of establishing the acceleration structure.

26. (New) The apparatus of claim 25 wherein, the acceleration structure computation unit is further configured to compute, if the affirmative decision is not possible, a conservative decision as to whether the triangle overlaps the node and store the conservative decision as part of establishing the acceleration structure.

27. (New) The apparatus of claim 24 wherein the ray-casting module further comprises a traversal unit, the traversal unit operatively configured to:

compute a three dimensional ray space occupied by a ray according to the ray's increasing distance from a virtual source; and

traverse the ray space through the acceleration structure from the virtual source of the ray through an increasing virtual distance from the virtual source of the ray.

28. (New) The apparatus of claim 27 wherein the ray space traversed is a selected one of a cone or a pyramid.

29. (New) The apparatus of claim 27 wherein the acceleration structure further comprises at least one acceleration structure node, each node being associated with a region of node space; and wherein the ray casting module is further configured to store simplified geometry data associated with each acceleration structure node; and, when the ray space overlaps a majority of the node space, compute ray-object intersection using the simplified geometry data.

30. (New) The apparatus of claim 24 wherein the ray-casting module further comprises:

a matrix unit;

a transformation unit; and

a ray casting unit,

wherein the matrix unit is operatively configured to send affine transformation matrices of object data to the transformation unit, each affine transformation matrix being a selected one of an object-space transformation matrix and a normalized space transformation matrix, and the transformation unit is further operatively configured to receive a ray from the ray casting unit and transform the ray into the object's affine transformation matrix's coordinate system.

31. (New) The apparatus of claim 30 wherein the ray-casting module further comprises:

an acceleration structure computation unit operatively configured to subdivide the plurality of objects into an n-level hierarchy of objects and sub-objects and store data classifying the objects as primitive or non-primitive;

a traversal unit operatively configured to traverse a ray through the acceleration structure until a potential ray-object intersection is identified; and

an intersection computation unit;

wherein, the transformation unit is operatively configured to send the object's affine transformation matrix data and the transformed ray data to the transversal unit for recursive processing until the ray intersects with a primitive object, if the object identified by the traversal unit is not a primitive object; and

wherein, the transformation unit is operatively configured to send the object's affine transformation matrix data and the transformed ray data to the intersection computation unit, if the object identified by the traversal unit is a primitive object.

32. (New) An article of manufacture comprising a tangible computer-accessible storage medium for digitally storing a plurality of programming instructions designed to program an apparatus to render three-dimensional scenes by means of ray-tracing, wherein the programming instructions, if executed by the apparatus, enable the apparatus to:

establish ray tracing acceleration structures having a plurality of objects; and

prevent objects that have already been intersected by a ray during ray tracing from being intersected again by the ray.

33. (New) The article of manufacture of claim 32 wherein the programming instructions, if executed, further enable the apparatus to:

determine if an affirmative decision is possible as to whether a triangle within the ray-tracing acceleration structure overlaps a node of the acceleration structure, the decision being based at least in part on comparisons of the vertices of the triangle with the vertices of the node; and

if the affirmative decision is not possible, decide by making a conservative decision as to whether the triangle overlaps the node.

34. (New) The article of manufacture of claim 32 wherein the programming instructions, if executed, further enable the apparatus to:

compute a three dimensional ray space occupied by a ray according to the ray's increasing distance from a virtual source;

traverse the ray space through the acceleration structure; and
process selected objects identified within the ray space.

35. (New) The article of manufacture of claim 34 wherein the ray space traversed by the ray is a selected one of a cone or a pyramid, and the programming instructions, if executed, further enable the apparatus to process the objects within the ray space, and order the objects according to the objects' virtual distances from the virtual source of the ray.

36. (New) The article of manufacture of claim 34 wherein the acceleration structures have at least one acceleration structure node, each node being associated with a region of node space; and wherein the programming instructions, if executed, further enable the apparatus to:

store simplified geometry data associated with each acceleration structure node; and

when the ray space overlaps a majority of the node space, compute ray-object intersection, using the simplified geometry data.

37. (New) The article of manufacture of claim 32 wherein the programming instructions, if executed, further enable the apparatus to:

subdivide the plurality of objects into an n-level hierarchy of objects and sub-objects;

classify the objects as primitive or non-primitive;

traverse a ray through the acceleration structure until an intersected object is identified,

if the identified object is not a primitive object, store affine transformation data which transforms the object and ray into a coordinate system locally associated with the identified object, and traverse the transformed ray through the local coordinate system and store affine transformation data, recursively, until the ray intersects with a primitive object; and

if the identified object is a primitive object, store transformation data which transforms the primitive object and ray into a normalized object space locally associated with the identified object, intersect the transformed ray with the transformed identified object, and store ray-object intersection data.

38. (New) The article of manufacture of claim 32 wherein the programming instructions, if executed, further enable the apparatus to:

subdivide the plurality of objects into an n-level hierarchy of objects and sub-objects;

recursively instantiate a plurality of sub-objects, the sub-objects having a similar geometry; and

build a next level object by, at least in part, using the plurality of instantiated sub-objects with similar geometry.

39. (New) A ray casting processor for rendering dynamic three-dimensional scenes, the processor comprising:

a traversal unit, the traversal unit being coupled to a plurality of node caches for storing acceleration structure node data, the node data structured to improve accessibility according to ray coherence, the node caches arranged in an n-level hierarchy;

a list unit, the list unit being coupled to a plurality of list caches for storing lists of object addresses for objects that have already been intersected by a ray, the list caches arranged in an n-level hierarchy, the list unit having a decision unit, the decision unit configured to prevent objects or triangles from being intersected by the ray more than once; and

a matrix loading unit, the matrix loading unit being coupled to a plurality of matrix caches for storing affine transformations in the form of matrices, the matrix caches arranged in an n-level hierarchy.